

SPECIFICATIONS VISION15I-E (EASYCLICK)



	FEATURE	15I-E
DISPLAY	DISPLAY TYPE	TFT
	DIAGONAL (ACTIVE AREA)	15"
	VIEWABLE IMAGE SIZE (VIS)	304,1 X 228,1 MM
	RESOLUTION	1024X768 PIXELS
	COLORS	16,2 MILLION
	CONTRAST RATIO	500:1
	BRIGHTNESS	420 CD/M2
	VIEWING ANGLE (LEFT, RIGHT)	80, 80
	VIEWING ANGLE (UP, DOWN)	50, 80
	BACKLIGHT LIFETIME	38000 HRS
	OPTION BACKLIGHT DIMMING	ON REQUEST
	RESPONSE TIME (RISE/FALLING)	20/25 MS
	DOT PITCH	0,297X0,297 MM
	HORIZONTAL FREQUENCY	75 KHZ
	VERTICAL FREQUENCY	60 HZ
VGA INPUT TERMINAL	15 PIN DSUB-HD	
ELECTRICAL	POWER SOURCE	12VDC (INCL. SWITCH MODE PS 115/230 VAC)
	OPTIONAL VOLTAGE CONVERTER	24VDC → 12VDC (ISOLATED)
	POWER CONSUMPTION	32 WATT
	INLET PLUG DC POWER	3 PIN HIROSE
MECHANICAL	DIMENSIONS FRONT (W X H X D)	400 X 324 X 4,8 MM
	DIMENSIONS CHASSIS (W X H X D)	376 X 286 X 48,6 MM
	WEIGHT	5,05 KG
CHASSIS	FRONT	STEEL, RUGGED POWDER COATED
	FRONT COLOR	RAL 9005 (OR ON REQUEST)
	SEALING FRONT	IP65
	ENCLOSURE	STEEL / ALUMINIUM
	MOUNTING	PANEL MOUNT
ENVIRONMENTAL	OPERATING TEMPERATURE	0 – 50 °C
	STORAGE TEMPERATURE	-20 – 60 °C
CONTROL	PARAMETER ADJUSTMENT	OSD BUTTONS AT BACKSIDE
	POWER ON/OFF	POWER SWITCH AT BACK
OPTIONAL	CAPACITIVE TOUCH	
	RESISTIVE TOUCH	
	RAL COLOR	
	VIDEO (S-VIDEO/COMPOSITE VIDEO)	
	DVI	