

SPECIFICATIONS PANEL MOUNT VISION 12 I-K



	FEATURE	10I-K
DISPLAY	DISPLAY TYPE	TFT
	DIAGONAL (ACTIVE AREA)	12.1"
	VIEWABLE IMAGE SIZE (VIS)	246 X 185 MM
	RESOLUTION	800X600 PIXELS
	COLORS	262.144
	CONTRAST RATIO	200:1
	BRIGHTNESS	300 CD/M2
	VIEWING ANGLE (LEFT, RIGHT)	60, 60
	VIEWING ANGLE (UP, DOWN)	40, 55
	BACKLIGHT LIFETIME	50000 HRS
	OPTION BACKLIGHT DIMMING	ON REQUEST
	RESPONSE TIME (RISE/FALLING)	20/40 MS
	DOT PITCH	0,330X0,330 MM
	HORIZONTAL FREQUENCY	75 KHZ
	VERTICAL FREQUENCY	60 HZ
VGA INPUT TERMINAL	15 PIN DSUB-HD	
ELECTRICAL	POWER SOURCE	12VDC (INCL. SWITCH MODE PS 115/230 VAC)
	OPTIONAL VOLTAGE CONVERTER	24VDC → 12VDC (ISOLATED)
	POWER CONSUMPTION	38 WATT
	INLET PLUG DC POWER	Ø2,1/L9,5
MECHANICAL	DIMENSIONS FRONT (W X H X D)	347 X 280 X 4,8 MM
	DIMENSIONS CHASSIS (W X H X D)	315 X 235 X 47 MM
	WEIGHT	3,5 KG
CHASSIS	FRONT	STEEL, RUGGED POWDER COATED
	FRONT COLOR	RAL 9005 (OR ON REQUEST)
	SEALING FRONT	IP65
	ENCLOSURE	STEEL / ALUMINIUM
	MOUNTING	PANEL MOUNT
ENVIRONMENTAL	OPERATING TEMPERATURE	0 – 50 °C
	STORAGE TEMPERATURE	-20 – 60 °C
CONTROL	PARAMETER ADJUSTMENT	OSD BUTTONS AT BACKSIDE
	POWER ON/OFF	POWER BUTTON (OSD) AT BACK
OPTIONAL	CAPACITIVE TOUCH	
	RESISTIVE TOUCH	
	RAL COLOR	
	VIDEO (S-VIDEO/COMPOSITE VIDEO)	
	DVI	