

SPECIFICATIONS PANEL MOUNT VISION18I-K



	FEATURE	IK18
DISPLAY	DISPLAY TYPE	TFT
	DIAGONAL (ACTIVE AREA)	18,1"
	VIEWABLE IMAGE SIZE (VIS)	359 X 287,2 MM
	RESOLUTION	1280X1024 PIXELS
	COLORS	16,2 MILLION
	CONTRAST RATIO	350:1
	BRIGHTNESS	250 CD/M2
	VIEWING ANGLE (LEFT, RIGHT)	80, 80
	VIEWING ANGLE (UP, DOWN)	80, 80
	BACKLIGHT LIFETIME	40000 HRS
	OPTION BACKLIGHT DIMMING	ON REQUEST
	RESPONSE TIME (RISE/FALLING)	15/25 MS
	DOT PITCH	0,280X0,280 MM
	HORIZONTAL FREQUENCY	65 KHZ
	VERTICAL FREQUENCY	60 HZ
VGA INPUT TERMINAL	15 PIN DSUB-HD	
ELECTRICAL	POWER SOURCE	12VDC (INCL. SWITCH MODE PS 115/230 VAC)
	OPTIONAL VOLTAGE CONVERTER	24VDC → 12VDC (ISOLATED)
	POWER CONSUMPTION	44 WATT
	INLET PLUG DC POWER	Ø2,1/L9,5
MECHANICAL	DIMENSIONS FRONT (W X H X D)	482,6 X 399 X 4,8 MM
	DIMENSIONS CHASSIS (W X H X D)	442,5 X 359,1 MM
	WEIGHT	7,1 KG
CHASSIS	FRONT	STEEL, RUGGED POWDER COATED
	FRONT COLOR	RAL 9005 (OR ON REQUEST)
	SEALING FRONT	IP65
	ENCLOSURE	YELLOW PASSIVATED STEEL / ALUMINIUM
	MOUNTING	PANEL MOUNT
ENVIRONMENTAL	OPERATING TEMPERATURE	0 – 50 °C
	STORAGE TEMPERATURE	-20 – 60 °C
CONTROL	PARAMETER ADJUSTMENT	OSD BUTTONS AT BACKSIDE
	POWER ON/OFF	BUTTON AT BACK
OPTIONAL	CAPACITIVE TOUCH	
	RESISTIVE TOUCH	
	RAL COLOR	
	VIDEO (S-VIDEO/COMPOSITE VIDEO)	
	DVI	